



ZESTAWIENIE STALI

NIMNE ELEMENTU	WZMACZ [mm]	GRUBSZA [mm]	CIENIOK [mm]	CIĘŻAR [g]	OC. ROZMIAR [mm]	WAGA [g]	WŁ. WŁ. [g/cm ³]	WŁ. WŁ. [g/cm ³]	WŁ. WŁ. [g/cm ³]	POC. WŁ. [g/cm ³]	POC. WŁ. [g/cm ³]	POC. WŁ. [g/cm ³]
1-3	RS5/3	119,5	513	1	11,2	4,11	48,92	48,92	0,2	2,38	2,38	
4-8	PR05/3	333,37	513	1	33,33	8,82	293,84	293,84	0,4	13,33	13,33	
9	BL 10/200	220	513	3	1,20	15,7	1,14	18,64	0,42	0,08	0,5	
10	6 16	590	513	3	1,77	1,58	0,93	2,79	0,05	0,03	0,09	
11	BL 10/65	250	513	3	0,25	5,1	1,28	3,13	0,15	0,04	0,11	
12	BL 10/65	110	513	3	0,33	5,1	0,56	1,89	0,15	0,02	0,05	
WZMACN. x 1							369,3				18,46	
WZMACN. x 1							369,3				18,46	

BETON KSZTAŁTOWNIKI STALOWE ELEKTRODY KOTWY ZAPRAWA SYSTEMOWA HILTI HY-150	B20 S35X EA1.46 M12 M12
--	-------------------------------------

[illegible]